

## **LISTING OF CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Currently Amended) A spacer configured to mount a fan housing to a surface of a structural support, the spacer comprising:

a body;

a first aperture passing through the body, the first aperture having a first length through the body; ~~and~~

a second aperture passing through the body, the second aperture having a second length through the body, the second length different than the first length; and

a third aperture passing through the body, the third aperture having a third length through the body, the third length different than the first length and the second length;

wherein the body has a first orientation with respect to the fan housing and structural support in which the body separates the fan housing from the surface of the structural support by the first length when installed with a fastener passed through the first aperture and into the structural support; ~~and~~

wherein the body has a second orientation with respect to the fan housing and structural support in which the body separates the fan housing from the surface of the structural support by the second length when installed with a fastener passed through the second aperture and into the structural support; and

wherein the body has a third orientation with respect to the fan housing and structural support in which the body separates the fan housing from the surface of the structural support by the third length when installed with a fastener passed through the third aperture and into the structural support.

2. (Cancelled)

3. (Original) The spacer of claim 1, wherein an end of the first aperture is tapered for guiding a fastener into the first aperture.

4. (Currently Amended) The spacer of claim 1, wherein the body is ~~injection molded~~ constructed of a plastic material, and the first and second apertures are ~~formed during molding of~~ integrated into the body.

5. (Currently Amended) The spacer of claim 1, wherein the body includes an outwardly extending protrusion for orienting the spacer with respect to the fan housing in at least one of the first, second, and third ~~and second~~ orientations.

6. (Currently Amended) The spacer of claim 1, wherein the first aperture and second ~~apertures~~ aperture lie in planes that are substantially perpendicular to one another.

7. (Original) The spacer of claim 1, wherein the body includes:  
a first mounting surface engageable with the housing when the body is in the first orientation; and  
a second mounting surface engageable with the housing when the body is in the second orientation, the first mounting surface being substantially perpendicular to the second mounting surface.

8. (Original) The spacer of claim 7, further comprising a lip extending outwardly from the body, the lip preventing orientation of the spacer in a third orientation in which the first mounting surface is flush with the surface of the structural support.

9. (Original) The spacer of claim 8, wherein the lip prevents orientation of the spacer in a fourth orientation in which the second mounting surface is flush with the surface of the structural support.

10. (Currently Amended) A spacer configured to mount a fan housing to a web portion of a structural support, the spacer comprising:

a body defining a first aperture, ~~and a second aperture, and a third aperture~~ extending in different directions through the body, the body positionable in a first orientation between the web portion and the housing to mount the fan housing on the structural support, ~~and positionable~~ in a second orientation between the web portion and the fan housing to mount the fan housing on the structural support, and in a third orientation between the web portion and the housing to mount the fan housing on the structural support, the body including

a first mounting surface engageable with the fan housing when the body is in the first orientation, the first aperture extending through the first mounting surface and dimensioned to receive a fastener to connect the fan housing in spaced relationship to the web when the body is in the first orientation; ~~and~~

a second mounting surface engageable with the fan housing when the body is in the second orientation, the second aperture extending through the second mounting surface and dimensioned to receive a fastener to connect the fan housing in spaced relationship to the web when the body is in the second orientation; and

a third mounting surface engageable with the fan housing when the body is in the third orientation, the third aperture extending through the third mounting surface and dimensioned to receive a fastener to connect the fan housing in spaced relationship to the web when the body is in the third orientation;

wherein the fan housing is spaced a first distance, substantially equal to a length of the first aperture, from the web in the first orientation of the body, ~~and a second distance, substantially equal to a length of the second aperture,~~ from the web in the second orientation of the body, the second distance different than the first distance, and a third distance, substantially equal to a length of the third aperture, from the web in the third orientation of the body, the third distance different from the first distance and the second distance.

11. (Cancelled)

12. (Original) The spacer of claim 10, wherein an end of the first aperture is tapered for guiding a fastener into the first aperture.

13. (Currently Amended) The spacer of claim 10, wherein the body is ~~injection molded~~ constructed of a plastic material, and the first and second apertures are ~~formed during molding of~~ integrated into the body.

14. (Original) The spacer of claim 10, wherein the body includes an outwardly extending protrusion for orienting the spacer with respect to the fan housing in at least one of the first and second orientations.

15. (Currently Amended) The spacer of claim 10, wherein the first aperture and second ~~apertures~~ aperture lie in planes that are substantially perpendicular to one another.

16. (Original) The spacer of claim 10, further comprising a lip extending outwardly from the body, the lip preventing mounting of the spacer in an orientation in which the first mounting surface is flush with the web.

17. (Original) The spacer of claim 16, further comprising a second lip extending outwardly from the second mounting surface, the second lip preventing mounting of the spacer in an orientation in which the second mounting surface is flush with the web.

18. (Currently Amended) A spacer for mounting a fan housing in positions spaced from a mounting surface of a structural support, the spacer comprising:

a body having a first dimension in a first orientation, ~~and~~ a second dimension in a second orientation different than the first orientation, and a third dimension in a third orientation different than the first orientation and the second orientation;

a first aperture defined in the body and shaped to receive a fastener through the body, the first aperture having a length passing through the body that is the same as the first dimension;

a second aperture defined in the body and shaped to receive a fastener through the body, the second aperture having a length passing through the body that is the same as the second dimension;

a third aperture defined in the body and shaped to receive a fastener through the body, the third aperture having a length passing through the body that is the same as the third dimension;

the spacer having

a first mounting orientation with respect to the fan housing and structural support in which the spacer separates the fan housing from the mounting surface of the structural support by a distance substantially the same as the first dimension; ~~and~~

a second mounting orientation with respect to the fan housing and structural support in which the spacer separates the fan housing from the mounting surface of the structural support by a second distance substantially the same as the second dimension, wherein the second distance is different than the first distance; and

a third mounting orientation with respect to the fan housing and structural support in which the spacer separates the fan housing from the mounting surface of the structural support by a third distance substantially the same as the third dimension, wherein the third distance is different than the first distance and the second distance.

Claims 19-21 (Canceled)